



# DIN 7980



Podkładka sprężysta do śrub  
 z łbem walcowym  
**A2 / A4**

| d1         | dla gwintu | waga<br>100 szt. (kg) | d2 max | h min | s   |  |
|------------|------------|-----------------------|--------|-------|-----|---|
| <b>3</b>   | M 3        | 0,010                 | 5,6    | 2     | 1   | 1000  |
| <b>3,5</b> | M 3,5      | 0,011                 | 6,1    | 2     | 1   | 1000  |
| <b>4</b>   | M 4        | 0,020                 | 7      | 2,4   | 1,2 | 1000  |
| <b>5</b>   | M 5        | 0,037                 | 8,8    | 3,2   | 1,6 | 1000  |
| <b>6</b>   | M 6        | 0,042                 | 9,9    | 3,2   | 1,6 | 1000  |
| <b>8</b>   | M 8        | 0,105                 | 12,7   | 4     | 2   | 1000  |
| <b>10</b>  | M 10       | 0,196                 | 16     | 5     | 2,5 | 500   |
| <b>12</b>  | M 12       | 0,228                 | 18     | 5     | 2,5 | 500   |
| <b>14</b>  | M 14       | 0,380                 | 21,1   | 6     | 3   | 200   |
| <b>16</b>  | M 16       | 0,594                 | 24,4   | 7     | 3,5 | 200   |
| <b>18</b>  | M 18       | 0,660                 | 26,4   | 7     | 3,5 | 200   |
| <b>20</b>  | M 20       | 1,230                 | 30,6   | 9     | 4,5 | 100   |
| <b>22</b>  | M 22       | 1,360                 | 32,9   | 9     | 4,5 | 100   |
| <b>24</b>  | M 24       | 1,810                 | 35,9   | 10    | 5   | 100   |
| <b>27</b>  | M 27       | 2,060                 | 38,9   | 10    | 5   | 100   |
| <b>30</b>  | M 30       | 3,200                 | 44,1   | 12    | 6   | 100   |