


# DIN 85

**EN 21580  
ISO 1580  
PN 82219**



Wkręt z łbem walcowym  
z nacięciem płaskim  
**A2 / A4**

<b>n</b>	0,4	0,5	0,6	0,8	1,0	1,2	1,2	1,6	2,0	2,5
<b>k</b>	1,0	1,3	1,6	1,8	2,1	2,4	3,0	3,6	4,8	6,0
<b>dk</b>	3,2	4,0	5,0	6,0	7,0	8,0	10,0	12,0	16,0	20,0

<b>d</b>	<b>M 1,6</b>	<b>M 2</b>	<b>M 2,5</b>	<b>M 3</b>	<b>M 3,5</b>	<b>M 4</b>	<b>M 5</b>	<b>M 6</b>	<b>M 8</b>	<b>M 10</b>
<b>l 3</b>	0,027		0,045	0,046						
<b>4</b>	0,030	0,018	0,030	0,050						
<b>5</b>	0,034	0,020	0,033	0,055	0,083	0,116				
<b>6</b>	0,038	0,021	0,036	0,059	0,089	0,124	0,227	0,360		
<b>8</b>		0,025	0,042	0,068	0,100	0,139	0,252	0,402		
<b>10</b>		0,029	0,048	0,077	0,112	0,155	0,276	0,437	0,938	
<b>12</b>		0,033	0,054	0,086	0,124	0,170	0,300	0,472	1,000	
<b>14</b>		0,095	0,095	0,095		0,186	0,325	0,510		
<b>16</b>		0,040	0,066	0,103	0,148	0,201	0,350	0,546	1,120	2,020
<b>18</b>			0,112	0,112		0,217	0,375	0,579	1,190	
<b>20</b>		0,048	0,078	0,121	0,172	0,232	0,400	0,614	1,260	2,220
<b>22</b>				0,130		0,248	0,425	0,649		
<b>25</b>			0,143	0,143	0,202	0,271	0,462	0,701	1,410	2,470
<b>28</b>				0,156		0,310		0,753		
<b>30</b>				0,165	0,232	0,348	0,524	0,790	1,570	2,720
<b>35</b>				0,187		0,387	0,586	0,878	1,730	2,970
<b>40</b>				0,209	0,292	0,426	0,648	0,915	1,890	3,220
<b>45</b>				0,183		0,464	0,710	1,050	2,050	3,470
<b>50</b>				0,183		0,502	0,772	1,140	2,210	3,720
<b>55</b>						0,531	0,834	1,230	2,370	3,970
<b>60</b>							0,896	1,320	2,530	4,220
<b>65</b>							0,958	1,410	2,690	4,470
<b>70</b>							1,020	0,748	2,850	4,720
<b>75</b>								1,590	3,010	4,970
<b>80</b>							1,144	1,680	3,170	5,220
<b>90</b>							1,278	1,860	3,490	
<b>100</b>							1,544	2,280	4,420	5,220
	1000	1000	1000	1000	1000	1000 od l25 500	500 od l25 200	200 od l35 100	100	100

Waga 100 sztuk /kg